

# ENVIROLOGIC<sup>®</sup> HIGH-TACK GREASE 2

SOLVE SMARTER. WITH SIMPLICITY. WITHOUT COMPROMISE.



ENVIROLOGIC<sup>®</sup> High-Tack Grease 2 is an adhesive, biodegradable lubricant that can be used in a variety of applications to reduce wear and friction. This grease was specifically designed to seal out contaminants like water and debris in high speed applications.



ENVIROLOGIC<sup>®</sup> High-Tack Grease 2 is a VGP-compliant grease for use in Cutter Suction Dredge and Jack Up Boat applications. This grease was designed to adhere to metal surfaces using highly effective polymers developed specifically for RSC Bio Solutions. The steel and copper corrosion inhibitors and the performance additives in ENVIROLOGIC<sup>®</sup> High-Tack Grease 2 will provide a barrier to corrosion and wear that will extend the life of the equipment to which it is applied.

PROPERTY	ENVIROLOGIC <sup>®</sup> High-Tack Grease 2
NLGI GRADE	2
WORKED PENETRATION (MM/10), ASTM D 217	275
COLOR	TAN
TEXTURE	TACKY-SMOOTH
THICKENER	LITHIUM COMPLEX
DROPPING POINT (°C), ASTM D 2265	>260
BASE OIL TYPE	HEPR
FOUR BALL WELD (KGF), ASTM D 2596	500
FOUR BALL WEAR (MM), ASTM D 2266	0.41
WATER SPRAY OFF (% LOSS), ASTM D 4049	8
WATER WASHOUT (% LOSS), ASTM D 1264	6
STEEL CORROSION (WATER), ASTM D 1743	PASS
STEEL CORROSION (5% SYNTHETIC SEA WATER), ASTM D 5969	PASS
COPPER CORROSION, ASTM D 4048	1B

SERVING OFFSHORE + GLOBAL MARINE + DREDGING + CONSTRUCTION

