

HIGH PERFORMANCE, ECOLABEL CERTIFIED ISO 100 HYDRAULIC FLUID

Description

RSC *FUTERRA* HF 100 is a synthetic, Ecolabel, ISO 100 grade hydraulic fluid formulated to withstand extreme conditions and corrosion while operating in severe outdoor environments. It is intended for severe service, extreme high temperature (250°F/121°C), low temperature (-40°F/-40°C) and high pressure (5000+psi/34,470 kPa) applications.

Its excellent oxidative and hydrolytic stability and near zero foaming tendency ensure that the fluids will last much longer than other EALs and conventional oils. RSC *FUTERRA* HF 100 offers greater flexibility and the ultimate system compatibility – offering drop-in replacement and broad seal compatibility. It was formulated for industrial applications where incidental environmental exposure of the lubricant is a cause for concern, as it is readily biodegradable and non-sheening*.

RSC *FUTERRA* HF series meets the requirements for a growing list of manufacturers. Visit our [website](#) or contact customer service for a full list of OEM approvals.

Property	Method	Requirements	Result
Kinematic Viscosity			
At 40°C, cSt	D445	90-110	100
At 100°C, cSt	D445		14.9
Viscosity Index	D2270	90 min	154
Density(60°F)	D1298	report	0.845
Pour Point, °C	D97	-15 max	-51
Flash Point (COC), °C	D92	185 min	234
Acid Number, mgKOH/g	D664	Report	0.89
Steel Pin Corrosion (3 hours, 100°C)	D665	Pass	
Deionized Water			Pass
Synthetic Salt Water			Pass
Foam Properties (after 10 minutes)	D892		
Sequence I, mL	Tendency/Stability	50-0 max	0-0
Sequence II, mL	Tendency/Stability	50-0 max	10-0
Sequence III, mL	Tendency/Stability	50-0 max	0-0
Demulse Properties (82°C)	D1401		
Oil / Water / Emulsion		40/37/3	40 / 40 / 0
Minutes		30	10
Copper Corrosion	D130		
3hrs @ 100 °C		2 max	1a

HIGH PERFORMANCE, ECOLABEL CERTIFIED ISO 100 HYDRAULIC FLUID

Property	Method	Requirements	Result
Oxidation Mins to 25 psi loss	D2272		1200
Oxidation	D943		>1000 hrs
Oxidation	D943M		>9000 hrs
FZG		10 min.	12
Hydrolytic Stability	D2619		
Copper Weight Loss, mg/cm ³			0.00
Change in Acid Number, mgKOH/g			<4.0
Appearance of Copper Panel			1b
Vickers 35VQ25 Vane Pump	35VQ25		Pass
Vickers V104C Vane Pump			
Total loss of ring and vane, mg			Pass
Denison T6H20C Pump (HF-1, HF-2, HF-6)			Pass
Biodegradability, % in 28 Days			>60
Ecotoxicity			
Fathead minnow, 96h LC50, ppm	OECD 201	>100	>10,000
Daphnia magna, 48h EC50, ppm	OECD 202	>100	>10,000
Algae, 72h EC50, ppm	OECD 203	>100	>1,000
Elastomer SRE-NBR-1 (80°C 1000 hours)	ISO 6072		Pass
Elastomer HNBR (100°C 1000 hours)	ISO 6072		Pass
Elastomer FKM (100°C 1000 hours)	ISO 6072		Pass

*CFR40 Part 435B

NOTICE: While this information is presented in good faith and believed to be accurate, RSC Bio Solutions does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and RSC Bio Solutions disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

Updated: 12/21/16

For more information about RSC Bio Solutions, visit us at rscbio.com or call +1 704.684.6100.



KEEP MOVING. FORWARD.

rscbio.com



600 Radiator Road
Indian Trail, NC 28079-7643
800.661.3558
+1 704.684.6100

EnviroLogic® is a registered trademark of RSC Bio Solutions.
Copyright© 2016. RSC Bio Solutions. All Rights Reserved.